

Section 108113  
BIRD CONTROL DEVICES

**PART 1 – GENERAL**

**1.1 SUMMARY**

- A. This Section includes:
  - a. **WarBird Stainless Steel Bird Spikes** to prevent pest birds from landing, perching or roosting wherever the spikes are applied. They make surfaces uncomfortable, uninviting and intimidating to pest birds. WarBird Stainless Steel Spikes are safe, non-toxic, non-harmful, humane and eco-friendly.

**1.2 CONFORMANCE SUBMITTALS**

- A. Substitute Products: No substitute products will be accepted.
- B. Product Data: Submit manufacturer's samples, catalog cuts, shop sketches and other descriptive materials.

**1.3 CLOSEOUT SUBMITTALS**

- A. Maintenance Data

**1.4 QUALITY ASSURANCE**

- A. Single Source Responsibility: All primary products specified in this section will be supplied by a single manufacturer.
- B. Obtain technical literature from the specified manufacturer, telephone consultation and plan/photograph evaluation.
- C. Utilize labor or WarBird authorized installers who are certified in WarBird product installations. Proof of certification is required.

**1.5 PRODUCT HANDLING**

- A. Protect WarBird Stainless Steel Spikes from damage before, during and after installation.
- B. If damage occurs to WarBird Stainless Steel Spikes at any time, make all replacements immediately.

**1.6 WARRANTY**

- A. 10-year minimum warranty against material defects and workmanship

**PART 2 – PRODUCTS**

**2.1 ACCEPTABLE MANUFACTURER**

- A. **WarBird Manufacturing, Inc.,**  
1973 NJ-34, Wall Township, NJ 07719  
Email: [solutions@warbirdmfg.com](mailto:solutions@warbirdmfg.com)  
[www.warbirdmfg.com](http://www.warbirdmfg.com)

## **2.2 MODEL DESIGNATION**

- A. WarBird Stainless Steel Bird Spikes – Regular (STS)
- B. WarBird Stainless Steel Bird Spikes – Narrow (SLS)
- C. WarBird Stainless Steel Bird Spikes – Extra-Wide (EWS)

## **2.3 MATERIAL**

- A. **WarBird Stainless Steel Bird Spikes – Regular (STS)**
  - 1. Spikes: ST 302 Hard Surgical Grade Stainless Steel; resistant to virtually all weather and harsh environments.
  - 2. Base Strip: Flexible, UV-treated polycarbonate base with 360° bend.
  - 3. Number of spikes per 2ft section: 60
  - 4. Highest Point: 4.3"
  - 5. Base width: 0.5"
  - 6. Top width: 5"
- B. **WarBird Stainless Steel Bird Spikes – Narrow (SLS)**
  - 1. Spikes: ST 302 Hard Surgical Grade Stainless Steel; resistant to virtually all weather and harsh environments.
  - 2. Base Strip: Flexible, UV-treated polycarbonate base with 360° bend.
  - 3. Number of spikes per 2ft section: 36
  - 4. Highest Point: 4.3"
  - 5. Base width: 0.5"
  - 6. Top width: 1.5"
- C. **WarBird Stainless Steel Bird Spikes – Extra-Wide (EWS)**
  - 1. Spikes: ST 302 Hard Surgical Grade Stainless Steel; resistant to virtually all weather and harsh environments.
  - 2. Base Strip: Flexible, UV-treated polycarbonate base with 360° bend.
  - 3. Number of spikes per 2ft section: 60
  - 4. Highest Point: 4.3"
  - 5. Base width: 0.5"
  - 6. Top width: 7"

## **2.4 MOUNTING SYSTEMS**

- A. WarBird Bird Spikes Special Adhesive – for surfaces where screws or nails are not preferred
- B. Screws - #12 flat Philips-head screws
- C. Nails – 1/8" nails

## **PART 3 – EXECUTION**

### **3.1 EXAMINATION**

- A. Examine installation area. Notify Owner's Agent of detrimental work conditions.
- B. Do not proceed until conditions are corrected.

### **3.2 AREA AND SURFACE PREPERATION**

- A. Surfaces should be inspected and cleaned before beginning installation.
- B. Remove debris and make repairs as necessary – fallen tree branches, brush, peeling paint, loose parts, rubble, rust, etc.
- C. Use a microbial cleaning agent (WarBird EVO Cleaner) to clean and remove bird droppings and other residue from surfaces.
- D. Make sure surfaces are dry before installation.
- E. Remove or repair articles that may damage the WarBird Stainless Steel Bird Spikes after installation.

### **3.3 INSTALLATION**

- A. Install WarBird Stainless Steel Bird Spikes according to the WarBird installation instructions.
- B. Measure the length of each area to be covered, allowing for curves or bends in the surface. Based on length (multiply length by 2, 3 etc. if necessary for wider widths) order an appropriate amount of WarBird Stainless Steel Bird Spikes. Units may be 'snapped' to fit lengths less than 24".
- C. WarBird Spikes Special Adhesive – bond only to dry, clean surfaces, when temperature is between 32 degrees F and 120 degrees F. Apply a bead of adhesive to underside of base and firmly press WarBird Stainless Steel Bird Spikes onto surface so that it makes solid contact. Allow adhesive to dry and form a 'rivit' through the holes in the base.
- D. Screws – use #12 flat Philips-head screws and a screwdriver with a shaft of at least 4".
- E. Nails – use 1/8" nails and nail set.

### **3.4 INSPECTION**

- A. Visually inspect WarBird Stainless Steel Bird Spikes installation for inadequate adherence to surfaces, loose screws, or interfering debris.
- B. Make any necessary repairs immediately.